

FORMATTING OBJECTS

Pagination and Layout Formatting Objects § 6.4

root (layout-master-set, declarations?, page-sequence+) [§7.25.11]

declarations (color-profile)+

color-profile EMPTY [§7.28.7, 7.17.2-3]

page-sequence (title?, static-content*,flow) [§7.9.1-2, 7.24.1-4, 7.25.6-7, 7.25.9, 7.28.2]

layout-master-set (simple-page-master|page-sequence-master)+

page-sequence-master (single-page-master-reference|repeatable-page-master-reference|repeatable-page-master-alternatives)+ [§7.25.8]

single-page-master-reference EMPTY [§7.25.9]

repeatable-page-master-reference EMPTY [§7.25.9, 7.25.10]

repeatable-page-master-alternatives (conditional-page-master-reference+) [§7.25.10]

conditional-page-master-reference EMPTY [§7.25.9, 7.25.14, 7.25.12, 7.25.11]

simple-page-master (region-body, region-before?, region-after?, region-start?, region-end?) [§7.10, 7.25.8, 7.25.13, 7.25.15, 7.20.3, 7.27.7]

region-body EMPTY [§7.7, 7.10, 7.13.4, 7.20.1-3, 7.25.2-3, 7.25.17, 7.27.7]

region-before EMPTY [§7.7, 7.13.4, 7.20.1-3, 7.25.4, 7.25.16-17, 7.27.7]

region-after EMPTY [§7.7, 7.13.4, 7.20.1-3, 7.25.4, 7.25.16-17, 7.27.7]

region-start EMPTY [§7.7, 7.13.4, 7.20.1-3, 7.25.4, 7.25.17, 7.27.7]

region-end EMPTY [§7.7, 7.13.4, 7.20.1-3, 7.25.4, 7.25.17, 7.27.7]

flow (%block;^⓪)+ [§7.25.5]

static-content (%block;^⓪)+ [§7.25.5]

title (#PCDATA|^⓪inline)* [§7.4, 7.6-8, 7.11, 7.15.4, 7.17.1, 7.28.8]

Block-level Formatting Objects § 6.5

block (#PCDATA|^⓪inline;^⓪%block;^⓪)* [§7.4, 7.6-10, 7.12, 7.15.1-13, 7.17.1, 7.18.3, 7.19.1-7, 7.20.4, 7.27.4-5, 7.28.2, 7.28.8]

block-container (%block;^⓪)+ [§7.5, 7.7, 7.10, 7.13.4, 7.14.1, 7.14.4-5, 7.14.12, 7.18.3, 7.19.1-5, 7.20.1-4, 7.27.7, 7.28.2, 7.28.9]

Inline-level Formatting Objects § 6.6

bidirectional-override (#PCDATA|^⓪inline;^⓪%block;^⓪)* [§7.6, 7.8, 7.12, 7.15.4, 7.16.2, 7.16.8, 7.17.1, 7.27.1, 7.27.6, 7.28.2, 7.28.6]

character EMPTY [§7.6-9, 7.11-12, 7.13.1-3, 7.13.5, 7.15.4, 7.16.1-8, 7.17.1, 7.19.4-5, 7.27.2-5, 7.28.2, 7.28.6, 7.28.8]

initial-property-set EMPTY [§7.4, 7.6-8, 7.12, 7.15.4, 7.16.2, 7.16.4-6, 7.16.8, 7.17.1, 7.28.2, 7.28.6]

external-graphic EMPTY [§7.4, 7.6-7, 7.11-12, 7.13.1-5, 7.14.1-5, 7.14.10-12, 7.15.4, 7.15.9, 7.19.4-5, 7.20.1-2, 7.28.1-2, 7.28.7]

instream-foreign-object (The instream-foreign-object flow object has a child from a non-XSL namespace. The permitted structure of this child is that defined for that namespace.)

[§7.4, 7.6-7, 7.11-12, 7.13.1-5, 7.14.1-5, 7.14.10-12, 7.15.4, 7.15.9, 7.19.4-5, 7.20.1-2, 7.28.1-2]

inline (#PCDATA|^⓪inline;^⓪%block;^⓪)* [§7.4, 7.6-8, 7.11-12, 7.13.1-3, 7.13.5, 7.14.1, 7.14.4-5, 7.15.4, 7.15.13, 7.16.4, 7.17.1, 7.19.3-5, 7.28.2, 7.28.8]

inline-container (%block;^⓪)+ [§7.7, 7.11-12, 7.13.1-5, 7.14.1, 7.14.4-5, 7.14.12, 7.15.4, 7.19.3-5, 7.20.1-3, 7.27.7, 7.28.2]

leader (#PCDATA|^⓪inline;^⓪)* [§7.4, 7.6-8, 7.11-12, 7.13.1-3, 7.13.5, 7.15.4, 7.16.2, 7.16.5, 7.16.8, 7.17.1, 7.19.4-5, 7.21.1-6, 7.27.4-5, 7.28.2, 7.28.8]

page-number EMPTY [§7.4, 7.6-8, 7.11-12, 7.13.1-3, 7.13.5, 7.15.4, 7.15.13, 7.16.2, 7.16.4-6, 7.16.8, 7.19.4-5, 7.27.4-5, 7.28.2, 7.28.6, 7.28.8]

page-number-citation EMPTY [§7.4, 7.6-8, 7.11-12, 7.13.1-3, 7.13.5, 7.15.4, 7.15.13, 7.16.2, 7.16.4-6, 7.16.8, 7.19.4-5, 7.27.4-5, 7.28.2, 7.28.5-6, 7.28.8]

Formatting Objects for Tables § 6.7

table-and-caption (table-caption?, table) [§7.4, 7.6-7, 7.10, 7.12, 7.15.9, 7.18.3, 7.19.1-5, 7.26.7, 7.28.2]

table (table-column*,table-header?, table-footer?, table-body+) [§7.4, 7.6-7, 7.10, 7.12, 7.14.1, 7.14.4-5, 7.14.12, 7.18.3, 7.19.1-5, 7.26.1-6, 7.26.16-18, 7.27.7, 7.28.2]

table-column EMPTY [§7.7, 7.26.1-2, 7.26.4, 7.26.6, 7.26.8-9, 7.26.12-13, 7.28.8]

table-caption (%block;^⓪)+ [§7.4, 7.6-7, 7.12, 7.14.1, 7.14.4-5, 7.14.12, 7.18.3, 7.19.3, 7.28.2]

table-header (table-row+|table-cell+) [§7.4, 7.6-7, 7.12, 7.26.1-2, 7.26.4, 7.26.6, 7.28.2, 7.28.8]

table-footer (table-row+|table-cell+) [§7.4, 7.6-7, 7.12, 7.26.1-2, 7.26.4, 7.26.6, 7.28.2, 7.28.8]

table-body (table-row+|table-cell+) [§7.4, 7.6-7, 7.12, 7.26.1-2, 7.26.4, 7.26.6, 7.28.2, 7.28.8]

table-row (table-cell+) [§7.4, 7.6-7, 7.12, 7.14.1, 7.14.4, 7.19.1-5, 7.26.1-2, 7.26.4, 7.26.6, 7.28.2, 7.28.8]

table-cell (%block;^⓪)+ [§7.4, 7.6-7, 7.12, 7.13.4, 7.13.6, 7.14.1, 7.14.4-5, 7.26.1-2, 7.26.4, 7.26.6, 7.26.8, 7.26.10-11, 7.26.13-15, 7.28.2, 7.14.12]

Formatting Objects for Lists § 6.8

list-block (list-item+) [§7.4, 7.6-7, 7.10, 7.12, 7.19.1-5, 7.28.2, 7.18.3, 7.28.3-4]

list-item (list-item-label,list-item-body) [§7.4, 7.6-7, 7.10, 7.12, 7.19.1-5, 7.28.2, 7.18.3, 7.13.6]

list-item-body (%block;^⓪)+ [§7.4, 7.19.3, 7.28.2]

list-item-label (%block;^⓪)+ [§7.4, 7.19.3, 7.28.2]

Dynamic Effects: Link and Multi Formatting Objects § 6.9

basic-link (#PCDATA|^⓪inline;^⓪%block;^⓪)* [§7.4, 7.6-7, 7.11-12, 7.13.1-3, 7.13.5, 7.15.4, 7.19.3-5, 7.22.5-9, 7.22.12-14, 7.28.2]

multi-switch (multi-case+) [§7.4, 7.22.2, 7.28.2]

multi-case (#PCDATA|^⓪inline;^⓪%block;^⓪)* [§7.4, 7.22.3-4, 7.22.10, 7.28.2]

multi-toggle (#PCDATA|^⓪inline;^⓪%block;^⓪)* [§7.4, 7.22.11, 7.28.2]

multi-properties (multi-property-set+,wrapper) [§7.4, 7.28.2]

multi-property-set EMPTY [§7.22.1, 7.28.2]

Out-of-Line Formatting Objects § 6.10

float (%block;^⓪)+ [§7.18.1-2]

footnote (%inline;^⓪footnote-body) [§7.4]

footnote-body (%block;^⓪)+ [§7.4]

Other Formatting Objects § 6.11

wrapper (#PCDATA|^⓪inline;^⓪%block;^⓪)* [§7.28.2]

marker (#PCDATA|^⓪inline;^⓪%block;^⓪)* [§7.23.1]

retrieve-marker EMPTY [§7.23.2-4]

⓪ The parameter entity, "%block;" in the content models below, contains the following formatting objects:

block	table-and-caption	list-block
block-container	table	

⓪ The parameter entity, "%inline;" in the content models below, contains the following formatting objects:

bidirectional-override	inline	page-number-citation
character	inline-container	basic-link
external-graphic	leader	multi-toggle
instream-foreign-object	page-number	

The following formatting objects are "neutral" containers and may be used, provided that the additional constraints listed under each formatting object are satisfied, anywhere where #PCDATA, %block;, or %inline; are allowed:

multi-switch	wrapper
multi-properties	retrieve-marker

The following "out-of-line" formatting objects may be used anywhere where #PCDATA, %block;, or %inline; are allowed (except as a descendant of any "out-of-line" formatting object):

float

The following "out-of-line" formatting objects may be used anywhere where #PCDATA or %inline; are allowed (except as a descendant of any "out-of-line" formatting object):

footnote

FORMATTING PROPERTIES

Common Accessibility Properties § 7.4

1.source-document | 2.role

Common Absolute Position Properties § 7.5

1.absolute-position | 3.right | 5.left
2.top | 4.bottom

Common Aural Properties § 7.6

1.azimuth	7.pitch	13.speak-numeral
2.cue-after	8.pitch-range	14.speak-punctuation
3.cue-before	9.play-during	15.speech-rate
4.elevation	10.richness	16.stress
5.pause-after	11.speak	17.voice-family
6.pause-before	12.speak-header	18.volume

Common Border, Padding, and Background Properties § 7.7

1.background-attachment	20.border-top-style
2.background-color	21.border-top-width
3.background-image	22.border-bottom-color
4.background-repeat	23.border-bottom-style
5.background-position-horizontal	24.border-bottom-width
6.background-position-vertical	25.border-left-color
7.border-before-color	26.border-left-style
8.border-before-style	27.border-left-width
9.border-before-width	28.border-right-color
10.border-after-color	29.border-right-style
11.border-after-style	30.border-right-width
12.border-after-width	31.padding-before
13.border-start-color	32.padding-after
14.border-start-style	33.padding-start
15.border-start-width	34.padding-end
16.border-end-color	35.padding-top
17.border-end-style	36.padding-bottom

18.border-end-width	37.padding-left
19.border-top-color	38.padding-right

Common Font Properties § 7.8

1.Fonts and Font Data	4.font-size	7.font-style
2.font-family	5.font-stretch	8.font-variant
3.font-selection-strategy	6.font-size-adjust	9.font-weight

Common Hyphenation Properties § 7.9

1.country	3.script	5.hyphenation-character
2.language	4.hyphenate	6.hyphenation-push-character-count
		7.hyphenation-remain-character-count

Common Margin Properties-Block § 7.10

1.margin-top	3.margin-left	5.space-before	7.start-indent
2.margin-bottom	4.margin-right	6.space-after	8.end-indent

Common Margin Properties-Inline § 7.11

1.space-end	2.space-start
-------------	---------------

Common Relative Position Properties § 7.12

1.relative-position

Area Alignment Properties § 7.13

1.alignment-adjust	3.baseline-shift	5.dominant-baseline
2.alignment-baseline	4.display-align	6.relative-align

Area Dimension Properties § 7.14

1.block-progression-dimension	6.max-height	10.scaling
2.content-height	7.max-width	11.scaling-method
3.content-width	8.min-height	12.width
4.height	9.min-width	
5.inline-progression-dimension		

Block and Line-related Properties § 7.15

1.hyphenation-keep	8.space-treatment
2.hyphenation-ladder-count	9.text-align
3.last-line-end-indent	10.text-align-last
4.line-height	11.text-indent
5.line-height-shift-adjustment	12.white-space-collapse
6.line-stacking-strategy	13.wrap-option
7.linefeed-treatment	

Character Properties § 7.16

1.character	4.text-decoration	7.treat-as-word-space
2.letter-spacing	5.text-shadow	8.word-spacing
3.suppress-at-line-break	6.text-transform	

Color-related Properties § 7.17

1.color	2.color-profile-name	3.rendering-intent
---------	----------------------	--------------------

Float-related Properties § 7.18

1.clear	2.float	3.intrusion displace
---------	---------	----------------------

Keeps and Breaks Properties § 7.19

1.break-after	3.keep-together	5.keep-with-previous	7.widows
2.break-before	4.keep-with-next	6.orphans	

Layout-related Properties § 7.20

1.clip	2.overflow	3.reference-orientation	4.span
--------	------------	-------------------------	--------

Leader and Rule Properties § 7.21

1.leader-alignment	3.leader-pattern-width	5.rule-style
2.leader-pattern	4.leader-length	6.rule-thickness

Properties for Dynamic Effects Formatting Objects § 7.22

1.active-state	8.internal-destination
2.auto-restore	9.show-destination
3.case-name	10.starting-state
4.case-title	11.switch-to
5.destination-placement-offset	12.target-presentation-context
6.external-destination	13.target-processing-context
7.indicate-destination	14.target-stylesheet

Properties for Markers § 7.23

1.marker-class-name	3.retrieve-position
---------------------	---------------------

2.retrieve-class-name	4.retrieve-boundary
-----------------------	---------------------

Properties for Number to String Conversion § 7.24

1.format	2.grouping-separator	3.grouping-size	4.letter-value
----------	----------------------	-----------------	----------------

Pagination and Layout Properties § 7.25

1.blank-or-not-blank	7.initial-page-number	13.page-height
2.column-count	8.master-name	14.page-position
3.column-gap	9.master-reference	15.page-width
4.extent	10.maximum-repeats	16.precedence
5.flow-name	11.media-usage	17.region-name
6.force-page-count	12.odd-or-even	

Table Properties § 7.26

1.border-after-precedence	10.empty-cells
2.border-before-precedence	11.ends-row
3.border-collapse	12.number-columns-repeated
4.border-end-precedence	13.number-columns-spanned
5.border-separation	14.number-rows-spanned
6.border-start-precedence	15.starts-row
7.caption-side	16.table-layout
8.column-number	17.table-omit-footer-at-break
9.column-width	18.table-omit-header-at-break

Writing-mode-related Properties § 7.27

1.direction	4.text-orientation	6.unicode-bidi
2.glyph-orientation-horizontal	5.text-depth	7.writing-mode
3.glyph-orientation-vertical		

Miscellaneous Properties § 7.28

1.content-type	6.score-spaces
2.id	7.src
3.provisional-label-separation	8.visibility
4.provisional-distance-between-starts	9.z-index
5.ref-id	

Shorthand Properties § 7.29

1.background	9.border-spacing	17.page-break-before
2.background-position	10.border-top	18.page-break-inside
3.border	11.border-width	19.pause
4.border-bottom	12.cue	20.position
5.border-color	13.Font	21.size
6.border-left	14.margin	22.vertical-align
7.border-right	15.padding	23.white-space
8.border-style	16.page-break-after	24.xml:lang

Core Function Library

Number Functions § 5.10.1

numeric floor (numeric)	numeric min (numeric, numeric)
numeric ceiling (numeric)	numeric max (numeric, numeric)
numeric round (numeric)	numeric abs (numeric)
color rgb (numeric, numeric, numeric)	color system-color (NCName)
color rgb-icc (numeric, numeric, numeric, NCName, numeric, numeric)	

Font Functions § 5.10.2

object **system-font**(NCName, NCName?)

Property Value Functions § 5.10.3

object **inherited-property-value**(NCName?)
 numeric **label-end**()
 numeric **body-start**()
 object **from-parent**(NCName?)
 object **from-nearest-specified-value**(NCName?)
 object **from-table-column**(NCName?)
 numeric **proportional-column-width**(numeric)
 object **merge-property-values**(NCName?)



Quick Reference



W3C Recommendation
15 October 2001

<http://www.w3.org/TR/xsl/>

Table of Contents:

Formatting Objects

Formatting Properties

Core Function Library

deepX Ltd.

Dublin, Ireland

info@deepX.com
<http://www.deepX.com/>